

**MATERIAL SAFETY DATA SHEET**

**Company Details**

Name	Afrivet Business Management(Pty)Ltd	Emergency Phone Number	0860833278
Address	P.O Box 2009	Tel	+27(0)129916416
	Faerie Glen	Fax	+27(0)129916417
	0043		

**1.Product and Company Identification:**

<u>Trade / Commercial Name</u>	<b>ECOMECTIN 1% INJECTION</b>		
<u>Chemical Name</u>	ethyl alcohol, hfp , Ivermectin 1% , Propylene Glycol 72%		
<u>Formula</u>	C2H5OH		
<u>Chemical Family</u>	603 Alcohol's		
<u>Synonyms</u>	ethanol, grain alcohol, fermentation alcohol, alcohol, methylcarbinol, absolute alcohol		
<u>Un No</u>	1170	<u>Hazchem Code</u>	2[S]
<u>ERG No.</u>	127	<u>EAC</u>	26

**2.Hazards Identification:**

Flammable Liquid.  
Will be easily ignited by heat, sparks or flames.  
Fire may produce irritating, corrosive and/or toxic gases.  
May have irritant effect: on eyes, on skin, on air passages.  
Runoff from fire control may cause pollution.

**3.Composition:**

Hazardous Components ethyl alcohol, hfp

**4.First Aid Measures**

<u>First Aid Skin</u>	Remove & isolate contaminated clothing, including shoes. Flush body with plenty of water for at least 20 minutes. Wash skin with soap and water. 00Keep victim warm and quiet.
<u>First Aid Eyes</u>	Flush eyes with water for 15 minutes. Hold eyelids open while washing.
<u>First Aid Ingested</u>	Do not induce vomiting. Seek medical assistance.
<u>First Aid Inhalation</u>	Move victim to fresh air. If not breathing give artificial respiration. If breathing of victim is difficult administer oxygen for a maximum period of one hour.

**5.Fire Fighting Measures**

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.  
Small Fires: Dry chemical, CO2, water spray or alcohol-resistant foam.  
Large Fires: Water spray, fog or alcohol-resistant foam. Do not use straight streams.  
Move containers from fire area if you can do it without risk.  
Fire involving Tanks or Bulk Containers: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.  
Cool containers with flooding quantities of water until well after fire is out.  
Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.  
ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.  
Isolate spill or leak area immediately for at least 25 to 50 metres (80 to 160 feet) in all directions.  
Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.  
Wear positive pressure self-contained breathing apparatus (SCBA).

**MATERIAL SAFETY DATA SHEET**

Structural firefighters' protective clothing will only provide limited protection.  
 Large spill consider initial downwind evacuation for at least 300 metres (1000 feet).  
 If ROAD OR RAIL TANKER is involved in a fire, ISOLATE for 800 metres (1/2 mile) in all directions;  
 also, consider initial evacuation for 800 metres (1/2 mile) in all directions.

**6. Accidental Release Measures**

Breathing apparatus for fire only  
**PRECAUTIONS:**  
 Restrict access to area.  
 Provide adequate protective equipment and ventilation.  
 Remove sources of heat and flame.  
 Notify occupational and environmental authorities  
**SPILL OR LEAK:**  
 ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).  
 All equipment used when handling the product must be grounded.  
 Do not touch or walk through spilled material.  
 Stop leak if you can do it without risk.  
 Prevent entry into waterways, sewers, basements or confined areas.  
 A vapour suppressing foam may be used to reduce Vapours.  
 Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.  
 Use clean non-sparking tools to collect absorbed material.  
**Large Spills**  
 Dike far ahead of liquid spill for later disposal.  
 Water spray may reduce vapour; but may not prevent ignition in closed spaces.

**7. Handling And Storage**

Separation of at least 3M from the following classes is recommended.  
 Corrosives  
 Fire separation of at least 5M or 4Hr fire resistant wall  
 from the following classes is recommended.  
 Flammable Gases Flammable Solids  
 Spontaneously Combustibles Dangerous When Wet  
 Poison  
 Storage in the same room or space is prohibited with the following classes:  
 The rooms or spaces should be at least 10M apart.  
 Explosives Poisonous Gases  
 Oxidizing Agents Organic Peroxides  
 Radioactive

**8. Exposure Controls/Personal Protection**

<u>Occupational Exposure Limits</u>	T	W	A	OEL-RL	SHORT TERM	OEL-RL
	PPMa )			MG/M3b )	PPMa )	MG/M3b )
	1000			1900	-	-

**Controls**  
 The control measures appropriate for a particular worksite depend on how this material is used and on the extent of exposure.  
 The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release.  
 Use a non-sparking, grounded ventilation system separate from other exhaust ventilation systems. Exhaust directly to the outside.  
 Supply sufficient replacement air to make up for air removed.  
 Have a safety shower/eye wash fountain readily available in the immediate work area  
**Personal Protection**  
 If engineering controls and work practices are not effective in

**MATERIAL SAFETY DATA SHEET**

ECOMECTIN 1% INJECTION

controlling this material, then wear suitable personal protection equipment, including chemical safety goggles & face shield, boots, imperious gloves, coveralls, & respiratory protection.  
Have appropriate equipment available for use in emergencies.

**9. Physical & Chemical Properties**

A colourless volatile liquid with wine odour.

Boiling Point: 78 oC

Relative Density: vapour: 1,59 (air:1)

liquid: 0,79 (water:1)

Vapour Pressure: 5,6 kpa

Flash Point: 12 oC

Flammable Limits: 3,3 to 19%

Autoignition Temperature: 423 oC

Completely soluble in water.

Forms explosive mixtures with oxidising agents.

**10. Stability And Reactivity**

Conditions to Avoid

Stable.

Risk of violent reaction. Forms explosive mixtures with air. Hygroscopic.

Incompatible Materials

strong oxidizing agents, peroxides, acids, acid chlorides, acid anhydrides, alkali metals, ammonia, moisture.

Other

None.

**11. Toxicological Information**

Causes skin and eye irritation. Ingestion can cause nausea, vomiting and inebriation; chronic use can cause serious liver damage. Note that "absolute" alcohol, which is close to 100% ethanol, may nevertheless contain traces of 2-propanol, together with methan or benzene. The latter two are very toxic, while "denatured" alcohol has substances added to it which make it unpleasant and possibly hazardous to consume. Typical OEL 1000 mg/m<sup>3</sup>.

Toxicity data

ORL-CHD LDLO 2000 mg kg<sup>-1</sup>

ORL-MUS LD50 3450 mg kg<sup>-1</sup>

ORL-RAT LD50 7060 mg kg<sup>-1</sup>

ORL-RAT LD50 7060 mg kg<sup>-1</sup>

IHL-RAT LC50 20000 ppm/10h

**12. Ecological Information**

No data available.

**13. Disposal Considerations**

Disposal Method Product

There are no uniform EC regulations for the disposal of chemicals or residues.

Chemical residues generally count as special waste.

The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations.

We recommend that you contact the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste.

Disposal Method Packaging Disposal in accordance with local legal provisions.

**14. Transport Information**

UN No

1170

Hazchem Code

2[S]



**MATERIAL SAFETY DATA SHEET**

<u>ERG No.</u>	127	<u>EAC</u>	26
<u>IMDG-Shipping Name</u>	ETHANOL SOLUTION		
<u>IMDG Code</u>	3074	<u>IMDG-Packaging Group</u>	II/III
<u>Marine Pollutant</u>	Yes		
<u>Class</u>	Class: 3 Flammable Liquid Group: II/III		
<u>Subsidiary Risks</u>	None		

**15. Regulatory Information**

<u>EEC Hazard Classification</u>	3
<u>Risk Phrases</u>	R11 Highly flammable. R20 Harmful by inhalation. R22 Harmful if swallowed. R36 Irritating to eyes. R37 Irritating to respiratory system. R38 Irritating to skin.
<u>Safety Phrases</u>	S3 Keep in a cool place. S7 Keep container tightly closed. S9 Keep container in a well-ventilated place. S16: Keep away from sources of ignition - no smoking.
<u>National Legislation</u>	

**16. Other Information**

Reason for Alteration: General update.

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properness of the product.

**Disclaimer:**

\*\*\*\*\*

The company provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. THE COMPANY MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, THE COMPANY WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

\*\*\*\*\*

LAST PAGE